

UNLIMITED COVERAGE

Utilizing existing GSM networks, the SS388 offers unlimited coverage.

DISPATCHER

The platform offers dispatcher software that allows the customer to be in control of their own network.

PRIVATE CALLS

Private calls can be made by choosing the required radio id. The two radios will be entered into a private group. Once the conversation is over, the radios will automatically revert back into their original group.

STUN FUNCTION

The operator can stun a radio should the radio be stolen or abused. The radio can be reactivated by the controller.

GLOBAL POSITIONING SYSTEM

The SS388 offers GPS tracking via the dispatch station software, showing speed, distance travelled and time.

VOICE RECORDING

All communication is recorded on the platform and available for instant replay. Recordings remain available for a month and can be easily down loaded to customer server for storage.

GROUP CALLS

Group calls can be made by choosing the required radio id 's. The radios will be entered into a private group. Once the conversation is done, the radios will automatically revert back into their original groups.

SEND MESSAGES

The operator can send instant voice and text messages to a radio. All sent messages are recorded on the server.

Actual size



SPECIFICATION

ТҮРЕ	PARAMETER	SPECIFICATION
Mechanical properties	Model number	SS 388
	Dimension	120mm x 60mm x 40mm
	Weight	268g
	Working temp	-30deg to +75deg
Basic parameter	Working voltage	3.3v~4.2v (standard3.8v)
	Working current	250mA@UTMS 2100/900
		220mA@GSM900
	Peak current	0.8A
RF Parameter	WCDMA	band1:2100M band8:900M band5:850M (optional)
	GSM	GSM/GPRS:900M/1800M GSM/GPRS:850M/1900M
	Maximum output	WCDMA 900/2100MHz:power class 3
		(+24dBm+2.5dBm/-1.5dBm)
		GSM/GPRS 850/900MHz: power class4
		(+33dBm+2.5dBm/-0.5dBm)
		GSM/GPRS 1800/1900MHz: power class 1
		(+30dBm+2.5dBm/-0.5dBm)

DEALER CONTACT DETAILS:





